



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS
 2. THIN GOLD OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 3. BERYLLIUM COPPER
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 5. TEFLON

1. CRIMPED FERRULE
 HEX CRIMP SIZE ".1"
 2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	6/1	ISSUE	A	PART NO.	TITLE	
7	FERRULE			1	FR-16-30-87	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4					G.L.I. MCX R/A CRIMP JACK (FOR 1.37 O.D MICRO-CABLE)	
6	COVER			1	CV-405-08					APPROVED		DATE
5	INSULATOR	DELFIN	NATURAL	1	400-1112A1-5D							04-02-'14
4	CONTACT PIN			1	400-6112A1-4					CHECKED	DATE	DRAWING NO.
3	INSULATOR			1	400-6112A1-3-50T						04-02-'14	400-6112U1-32-50
2	BODY			1	400-6112A1-2					DRAWN	DATE	FILE NO.
1	HOUSING			1	400-6112U1-1					ANGELA	04-02-'14	R:\D\G\DWG\400\6112U1\32\50