



NOTE: 1. VSWR: 1.10 Max. @ 0~6 GHz

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BERYLLIUM COPPER  
 2. THIN GOLD OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK  
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK  
 4. TEFLON

RoHS COMPLIANT

**G.L.I.**

			DIMENSIONS ARE IN MILLIMETERS			PART NO.			TITLE		
			UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED					
			0.5-6 = ±0.2						03-16-'16		
			6-30 = ±0.4								
			30-120 = ±0.6						DATE		
			120-315 = ±1						03-16-'16		
			315-1000 = ±1.6						DRAWING NO.		
			1000-2000 = ±2.4						SMP-7071A2-50		
			SCALE 10/1			ISSUE A			FILE NO. R:\D\G\DWG\SMP\7071A2\50		

3	CONTACT PIN	NOTE 1	NOTE 3	1	SMP-7071A2-3
2	INSULATOR	NOTE 4	NATURAL	2	SMP-7071A2-2 -50T
1	BODY	NOTE 1	NOTE 2	1	SMP-7071A2-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.